

All Purpose Premix

All Purpose Premix compound is an economical, air-drying, lightweight compound suitable for all three coat applications or as a finishing coat for all plasterboard joints, angles and fastener heads. It is a premium grade product that can be used in conjunction with BaseCote™ or RediBase™ compounds.

ADVANTAGES

- Premium grade lightweight, all purpose or finishing compound
- May be used for all three coats or as a finishing coat
- Excellent workability, easy application by hand or with mechanical tools
- Minimal mixing and cleaning of tools
- OK to sand by hand or with mechanical sanding tools
- Excellent surface for painting

RECOMMENDED

- All Purpose Premix is suitable for use as all three coats in the USG Boral three coat jointing system
- All Purpose Premix is suitable for the final coating of plasterboard joints, angles and fastener heads when used in conjunction with USG Boral BaseCote™ or RediBase™ compounds

APPLICATION

- Surfaces must be clean and free from dust
- All Purpose Premix has a high viscosity in the pail; it may be diluted to a workable viscosity by adding water followed by mechanical mixing
- Can be applied with hand and mechanical tools
- When using All Purpose Premix for all three coats, the first coat must be used to bed a high quality paper tape
- All Purpose Premix compound must be allowed to dry thoroughly (approx. 24 hours) before re-coating or sanding
- Only apply over base compounds that have been allowed to dry thoroughly (24 hours)
- Sand with care lightly using 150, 180 or 220 grit paper
- Thoroughly clean all tools and equipment after use



ALL PURPOSE PREMIX SPECIFICATIONS

Feature	Description
Colour	White
Working Time	Drying Type: Minimum 24 hours drying time or longer in adverse climatic conditions
Packaging	18kg re-sealable pail
VOC	Less than 50g per litre
Manufacture	Low VOC compound manufactured to stringent USG Boral product quality specifications.

All Purpose Premix

INSTALLATION

Refer to USG Boral website USGBoral.com or call TecASSIST® on **1800 811 222**.

AVOID

- The application of All Purpose Premix compound at interior temperatures less than 10°C is not recommended.
- Under cold or wet weather conditions, allow more than 24 hours for thorough drying
- When diluting All Purpose Premix do not vigorously over mix as this will introduce entrapped air which can result in surface imperfections
- Do not apply All Purpose Premix over joints that are not thoroughly dry; pinholes may result
- Do not use sandpaper lower than 150 grit. Take care to avoid scratching when sanding
- The inclusion of other materials to a mix will impair the performance (e.g. reduced strength and poor adhesion) and void the product warranty

MIXING

- Always use clean tools
- Do not mix with residues of previously used compounds
- The inclusion of such materials will impair the performance of this product and will void the product warranty
- All Purpose Premix may appear thick in pail. Before adding water, lightly mix and test its application; if required, add water to achieve desired consistency
- **Caution:** Avoid over-thinning when adding water as this may cause cracking and excessive shrinkage
- If liquid has separated from the compound, stir carefully to restore consistency
- **Caution:** Do not overmix; overmixing can introduce air bubbles, which can create surface imperfections

STORAGE

- All Purpose Premix should be stored under cover in a dry environment and protected from temperature extremes; storage in an unsuitable environment can shorten the life of this product
- It is recommended that All Purpose Premix is used before the best before date displayed on the pail. It may still be usable after that date if stored unopened, in an appropriate environment

HEALTH & SAFETY

1. Dust from this product contains Silica. Prolonged inhalation may be harmful to health.
2. Ensure adequate ventilation. Wear eye protection and an approved disposable respirator which conforms to AS1716: 2012 Type P1 or P2.
3. If dust or paste causes irritation use impervious PVC, nitrile or rubber gloves. Wash exposed skin after handling. If product gets into the eyes, wash thoroughly with clean water.
4. Do not ingest contents of package. If ingested, seek medical advice immediately.
5. Keep contents out of reach of children.
6. Be conscious of the environment. Dispose of empty packaging in a responsible manner.
7. Follow safe lifting instructions on the product label.

REFERENCES

For further health and safety instructions, refer to the Material Safety Data Sheet for this product, available from your USG Boral sales office, TecASSIST® **1800 811 222** or USGBoral.com

In Emergencies Call **1800 033 111**

Poison Information **13 11 26**

SALES ENQUIRIES **1800 003 377** (AU)

TecASSIST® **1800 811 222** (AU)

0800 874 267 (NZ)

© 2017 USG BORAL. All rights reserved. The trademarks USG BORAL, INNOVATION INSPIRED BY YOU, TecASSIST and All Purpose Premix are trademarks of USG Boral Building Products or one or more of its affiliates.

This technical information is intended to provide general information on plasterboard products and should not be a substitute for professional building advice.

Product availability should be checked with your local USG Boral Sales office, as availability may vary.

We recommend you use a qualified person to install USG Boral plasterboard. Illustrations in this guide are only representative of USG Boral plasterboard products and the appearance and effects that may be achieved by their use. To ensure the information you are using is current, USG Boral recommends you review the latest building information available on the USG Boral website. USGBoral.com

USG Boral Building Products Pty Limited - ABN 84 004 231 976 - 251 Salmon Street, Port Melbourne, Vic. 3207

UB1003-1-COM 11/16