

TECHNICAL DATA

Regular

Regular® is standard core plasterboard encased in a strong 100% recycled paper liner, ideal for a wide range of residential and commercial internal wall and ceiling applications where fire resistance ratings, impact and water resistance are not required. Regular plasterboard is available in two types of edge profiles with lengths up to 6 metres to minimise jointing, providing a surface suitable to a wide range of decorative finishes.

ADVANTAGES

- Economical
- Available in 2 types of edge profiles
- Internal wall and ceilings applications
- Flat surface suitable for decorative finishes

INSTALLATION


Refer to USG Boral website www.usgboral.com/plasterboard or call TecASSIST on 1800 811 222.

SUSTAINABILITY

USG Boral products are manufactured from a combination of natural gypsum, and paper liner made from 100% reclaimed and recycled paper waste. Plasterboard waste can be reclaimed and recycled into new plasterboard, or reused as soil conditioner.

WASTE MANAGEMENT

Waste collection services are available to divert acceptable plasterboard waste away from landfill for recycling or re-processing for other uses. For information on waste collection services available, please contact your local USG Boral office.



BOARD SPECIFICATION

Feature	Description
Thickness	10mm & 13mm
Edge Profiles	Recessed edge, Square edge, Recessed edge/Square edge
Sheet Size (width x length)	1200 x (2400-6000mm), 1350 x (3600-6000mm) [Please refer to Size & Availability Chart for more sizes] Product availability: Certain products and sizes may only be available on order or in pack lots.
Paper Colour	Buff
Mass	6.8 kg/m ² (10mm), 8.6 kg/m ² (13mm) nominal
Fire Hazard Properties	Group 1 – in accordance with BCA Specification C1.10a Fire Hazard Properties – Floors, Walls and Ceilings
Combustibility	Non Combustible material as defined in BCA Deem-to-Satisfy Provisions C1.12
VOC	Less than 0.5mg/m ³ TVOC
GECA	N/A
Manufacture	Manufactured in Australia to the requirements of AS/NZS 2588:1998 Gypsum plasterboard and in accordance with AS/NZS ISO 9001:2008 – Quality management systems – Requirements

Regular

VOLATILE ORGANIC COMPOUNDS (VOC) AND FORMALDEHYDE MINIMISATION

USG Boral products, compounds and adhesive have been independently tested to confirm compliance with Green Star specification limits for VOCs and are formaldehyde free.

REFERENCES

Refer www.usgboral.com/regular for Material Safety Data Sheet, Volatile Organic Compound Emission details and other additional information.

SALES ENQUIRIES 1800 003 377

TecASSIST® 1800 811 222

Boral® is a registered trademark of Boral Limited, USG and the building blocks logo are trademarks of USG Corporation and are used under licence by USG Boral Building Products Pty Limited. USG, USG in stylised letters and the building blocks logo are trademarks belonging to United States Gypsum company or its related companies.

Firestop® Soundstop® and Impactstop® are registered trademarks of USG Boral Building Products Pty Limited in Australia, other countries, or both. If these and other USG Boral trademarks are marked on their first appearance in this information with trade mark symbols (® or ™), these symbols indicate Australian registered or common law trademarks owned by USG Boral and others at the time this information was published. Such trademarks may also be registered or common law marks in other countries.

This technical information is intended to provide general information on plasterboard products and should not be a substitute for professional building advice. We recommend you use a qualified person to install USG Boral plasterboard. Illustrations in this guide are only representative of USG Boral plasterboard products and the appearance and effects that may be achieved by their use. To ensure the information you are using is current, USG Boral recommends you review the latest building information available on the USG Boral website. www.usgboral.com

USG Boral Building Products Pty Limited – ABN 84 004 231 976
251 Salmon Street, Port Melbourne, Vic. 3207

BCC 12900 07. 2014