

USGBoral EasyJoint

USGBoral EasyJoint is a setting type compound used for treating gypsum board joints and fixing points.

JOINTING COMPOUND



Easyjoint provides excellent tape bonding strength, is exceptionally smooth to work with and the easy mixing saves time. Easyjoint has a consistent setting time and is relatively easy to sand, giving a high level of finish.

Product Usage Data :

Setting Time	180 minutes.
Mixing Ratio	2 parts of compound to 1 part of clean water (in kg.)
Coverage	One bag can cover approximately 65 sqm.
Storage	The product must be kept in dry conditions, away from moisture. The bag should be stored at an elevated position. Part open bags should be sealed, as moisture can accelerate the setting time.

Mixing procedure :




1. Always use clean water, tools and containers. Using dirty containers / tools may affect setting time.



2. Slowly add powder to water and mix for 2-3 minutes.


Tapered Edge Joints (3 easy steps) :

1st Coat




Apply Easyjoint of 150 mm width for joint reinforcement.

2nd Coat




Apply an even coat of Easyjoint of 200 mm width.

3rd Finishing Coat




Apply an even coat of Easyjoint of 300 mm width for finishing.


Square Edge Joints (3 easy steps) :



Apply Easyjoint of 300 mm width for joint reinforcement.



Apply an even coat of Easyjoint of 400 mm width.



Apply an even coat of Easyjoint of 500-600 mm width for finishing.

Note : All Gypsum board Joints require light sanding before painting.

*Available in 20kg bag