USH

Maintenance Guidelines

......

	Any removal or	r dismantling should be	carried out by a qu	alified installer approved by	USG Interiors	
Suspended Grid	DONN DX 24	icitee 15 mm narrow fa 4 mm faced two-way e: 0 x 600 mm; or 1200 x	xposed grid system			
		Cleaning Where practical, first re with a non-solvent bas		is then perform any necess aner.	ary cleaning maintena	ince
				a high quality solvent bas by the paint manufacture		
Perimeter Trim	DONN ML 3 DONN MS 3 DONN MSL DONN MXT	600 Wall Angle 600 Long Legged Wall 000 Shadowline Wall A 3600 Long Legged Sha 3600 Centricitee Wall A 600 Seismic Wall Chan	Angle adowline Wall Angle Angle	;		
	 Cleaning Where practical first remove ceiling panels then perform any necessary cleaning maintenance wit a non-solvent based commercial cleaner. 					
				h a high quality solvent ba I by the paint manufactu		
Metal Paint Colours	Wet Spray –	- Product Code : Colour Code :	262 Speedlac (1 34063 Pacific V	nitro-cellulose lacquer) Vhite NZ	PPG Industries	
	Powder Coa	ating – Product Code : Colour Code :		r matt RAIN Pacific White	PPG Industries	
Ceiling Panel	USG Orion,	Eclipse, Millennia, Mar	s, and all ClimaPlus	products.		
	 Cleaning Use a soft nozzle vacuum cleaner or a damp (not wet) soapy sponge. Wipe off any soap deposi with a clean damp sponge. 					
	 Painting To repaint, spray a thinned, non-bridging, vinyl-acrylic flat wall/ceiling paint (<i>Not applicable to viny faced products</i>). Note: The type of paint selected and the method of application can alter the acoustical performance (particularly Mars and Eclipse) and fire ratings of any acoustical product Therefore USG Interiors cannot guarantee that the modified panels will match the published performance. If in doubt, replace with the same specification panel. 					
	If removing from the ceiling system, panels should be handled with care to avoid damage, stored on a smooth, flat, dry, surface and stacked face-to-face and back-to-back. Panels should be protected from moisture, dust and damage.					
		When re-installing, if used, ensure hold-down clips are replaced, other than those panels designated for frequent access.				
G Australasia	© 2013		nsland Victoria) 226-215	Auckland Head Office Phone: (09) 270 2595	Christchurch	TMG