# **GLOSSY™ CLIMAPLUS™**



## FEATURES AND BENEFITS

- Elegant, Monolithic visual
- Superior Noise Reduction up to 0.90 NRC
- High Light reflectance
- Washable finish

# APPLICATIONS

- Conference Rooms
- Open plan offices
- Multiplexes, Cinema halls, Indoor Entertainment areas

# SUBSTRATE

Fiberglass






### Edge Panel Size<sup>1</sup> Class Item No. NRC Color **Grid Options** Recycled Content 0 0 4 .88 600x600x20mm Class A 20 White Α 40% S-BESK \_\_ A 20 White 600x1200x20mm Class A .90 40% 1200x1200x20mm Class A 20 White Α 40%

GRID PROFILE

**OPTIONS** 

GLOSSY PANELS



### PHYSICAL DATA/ **FOOTNOTES**

### ASTM E1264 Classification

Type III, Form 1, Pattern E,G

Metric Weight 2.25 - 3.00 kg/m²

### Thermal Resistance

R-1.7 (15mm Panels) R-2.0 (20mm Panels)

### Footnotes

- Custom-size panels available.
   Please contact your USG Boral Sales
   Representative for details.
- 2. LR values are shown as averages.
- Not all panel sizes available in all geographical areas, some metric sizes available to order.

Note:
Glossy ceiling tiles are also available in 25mm thickness. For more details please contact USG Boral Sales Representative.

### TRADEMARKS

TRADEMARKS
The trademarks GLOSSY, CLIMAPLUS, DXA, DXI, DXII and INNOVATION INSPIRED BY YOU are trademarks of USG Boral Building Products or one of more of its affiliates.

SAFETY FIRST!
Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

