

OLYMPUS™ MAX™ CLIMAPLUS™



OLYMPUS Max Panels with CLIMAPLUS Performance /
DONN DX/DXL Suspension System

FEATURES AND BENEFITS

- Nondirectional pattern reduces installation time and waste
- ClimaPlus™ 30-year lifetime system warranty to withstand conditions up to 49°C (120°F)/99% relative humidity without visible sag when used with a DONN® Brand suspension system.

APPLICATIONS

- Offices
- Classrooms
- Reception/Lobby areas
- Hotel
- Conference areas
- Retail stores

SUBSTRATE














































- Water-felted mineral fiber

 High Recycled Content


Fine-textured panel - Perforated





OLYMPUS™ MAX™ CLIMAPLUS


Edge	Panel Size ³	Class	Item No.	NRC	CAC Min.	LR ²	Color	Grid Options	VOC Emissions	Sag Resistance	Recycled Content ¹
SQ 	2' x 2' x 3/4" 600 x 600 x 19mm	Class A	40210 ME 40210	.70 	33 	.88 	White	A, B, C 	Low 		61% 
	2' x 4' x 3/4" 600 x 1200 x 19mm	Class A	40410 ME 40410	.70 	35 	.88 	White	A 	Low 		61% 
SLT 	2' x 2' x 3/4" 600 x 600 x 19mm	Class A	40220 ME 40220	.70 	33 	.88 	White	D 	Low 		61% 
	2' x 4' x 3/4" 600 x 1200 x 19mm	Class A	40420 ME 40420	.70 	35 	.88 	White	D 	Low 		61% 
FLB 	2' x 2' x 3/4" 600 x 600 x 19mm	Class A	40230 ME 40230	.70 	33 	.88 	White	E, F, G, H 	Low 		61% 
	2' x 4' x 3/4" 600 x 1200 x 19mm	Class A	40430 ME 40430	.70 	35 	.88 	White	E, F, G, H 	Low 		61% 

LEGEND









 **Low Emission (VOC Class)**
Meets the emission test criteria as low-emitting prescribed by the Singapore Green Building Council (SGBC), following ASTM D5116-06 testing methods

 **ClimaPlus Superior Performance**
Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew

 $\geq .70$ NRC

 $\geq .85$ LR

GRID PROFILE OPTIONS

A DX® DXI DXII DXIII	B Centricitee™ DXT™	C Omega™ DXM™	D DX® DXI DXII DXIII	E Omega™ DXM™	F Fineline® 1/8" DXFF™	G Fineline® DXF™	H Centricitee™ DXT™
							

PHYSICAL DATA/
FOOTNOTES

ASTM E1264 Classification
Type III, Form 2, Pattern C,E

ASTM E84 surface burning characteristics
Class A
Flame spread: 25
Smoke developed: 50

Imperial Weight
0.83-0.85 lb./ft²

Metric Weight
4.08-4.18 kg/m²

Thermal Resistance
R-1.7

Backloading
For details, see Ceiling Systems Warranties and Limitations (CW2015).

Maintenance
Can be cleaned easily with a soft brush or vacuum.

Footnotes

- For details, see LEED report tool at usgdesignstudio.com.
- LR values are shown as averages.
- Not all panel size available in all geographic areas, some metric sizes available to order.

- Short Specification:**
- Ceiling system shall comprise USG Olympus Max ClimaPlus™ high humidity / fire resistant acoustical ceiling panels in (DONN Centricitee 15mm [9/16"] / DONN DX 24mm [15/16"] / DONN Omega 14mm [9/16"] / DONN Fineline 15mm [9/16"] / DONN Identitee 15mm [9/16"]) exposed grid including wall trim as manufactured by USG Interiors, LLC.
 - Panels shall have NRC 0.70.
 - Panels shall have CAC 33-35.
 - Nominal size (600mm x 600mm / 600mm x 1200mm) x 19mm / (2' x 2' / 2' x 4') x 3/4".
 - Edge detail shall be (Fineline Bevel [FLB] / Shadowline Tapered [SLT] / Square Edge [SQ]).
 - Limiting Conditions - Maximum 49°C (120°F) and 99% RH.

TRADEMARKS

The trademarks CENTRICITEE, CLIMAPLUS, DONN, DX, DXF, DXFF, DXM OMEGA, DXI, DXT, FINELINE, IDENTITEE PIN PERF and INNOVATION INSPIRED BY YOU are trademarks of USG Boral Building Products or one of more of its affiliates.

SAFETY FIRST!

Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

ACT37 2015/8-15
© 2015 USG Boral. All rights reserved.

Manufactured, sold or distributed by USG Boral Building Products or one of more of its affiliates.
Persiaran Lagoon, Bandar Sunway, Petaling Jaya, Selangor, Malaysia 46150

USG BORAL SINGAPORE
8 Boon Lay Way #02-06 TradeHub 21
Singapore 609964
Tel: (65) 6272 9272 Fax: (65) 6278 5310



041-001-2474
Made From Recycled Material

www.usgboral.com

