

SPARTA™

(HEALTHCARE SERIES AVAILABLE)



Sparta Panels

FEATURES AND BENEFITS

- Laminated washable vinyl facing for easy maintenance
- Available only in plain facings with smooth appearance for plain white pattern and light texture for Star Plus pattern
- Ultra-high humidity resistant and sag resistance ensure durability in standard or extreme environmental conditions. May be installed early in the building programme
- Comes with aluminium foil backing which acts as a vapour barrier and resists breathing so panel stays cleaner longer
- Scrub resistant. Dirt marks are easy to remove
- Scuff and scratch resistant, for longer life
- Very suitable for healthcare applications
- Economical and easy to trim and install

APPLICATIONS

- Healthcare/laboratories
- Leisure/IT rooms
- Toilet/wet areas
- Department stores
- Retail showrooms






Texture - Plain White

Texture - Star Plus



SPARTA™

SPARTA PANELS

Edge	Panel Size	Item No.	NRC	CAC Min.	LR	Grid Options	VOC Emissions	Recycled Content	Anti-Mould & Mildew
SQ 	600 x 600 x 15mm 610 x 610 x 15mm	LSP665 LSP225	.15	35	.84	A, B	Low	32%	
	600 x 600 x 15mm 610 x 610 x 15mm	LPW665 LPW225	.15	35	.84	A, B	Low	32%	
	600 x 600 x 19mm 610 x 610 x 19mm	LSP669 LSP229	.15	36	.84	A, B	Low	32%	
	600 x 600 x 19mm 610 x 610 x 19mm	LPW669 LPW229	.15	36	.84	A, B	Low	32%	

LEGEND


Low Emission (VOC Class)

Meets the emission test criteria as low-emitting prescribed by the Singapore Green Building Council (SGBC) following ASTM D5116-06 testing methods.

ClimaPlus Superior Performance

Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mould and mildew.

GRID PROFILE OPTIONS



PHYSICAL DATA

General

Provide acoustical ceiling material manufactured to meet requirements of this specification in accordance with ASTM E1264.

Material

Acoustical ceiling units:

1. Type X, Pattern [G]
2. Smooth and textured laminated panels
3. Size 15, 19mm thick x [600 x 600]
4. Edge Detail Trim (Square)
5. Noise Reduction Coefficient (NRC) [0.15]
6. Ceiling Attenuation Class (CAC) [35] [36]
7. Light Reflectance Coefficient (LR) 0.84
8. Recycled Content [32%]
9. Colour white similar to RAL 9010
10. Thermal Resistance: 0.23 m² °K/W-R 1.3 (15mm), 0.31 m² °K/W-R 1.8 (19mm)
11. Humidity Resistance Maximum 95% RH/40°C
12. Weight: 3.5kg/m² 15mm, 4.5kg/m² 19mm
13. Mould prevention: inherent to mould/mildew growth
14. Relevant LEED Credit: EA Credit 1 | MR Credit 4 | MR Credit 5 | MR Credit 6 | IEQ Credit 3 | IEQ Credit 3.2 | IEQ Credit 4.6 | IEQ Credit 8.1 | IEQ Credit 9
15. Manufacturer subject to compliance with USG Boral terms and conditions
16. Product name [Sparta]

TRADEMARKS

The trademarks ClimaPlus, DONN and INNOVATION INSPIRED BY YOU are trademarks of USG Boral Building Products or one of more of its affiliates.

SAFETY FIRST!

Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

Manufactured, sold or distributed by USG Boral Building Products or one or more of its affiliates.
Persiaran Lagoon, Bandar Sunway, Petaling Jaya, Selangor, Malaysia 46150

USG BORAL SINGAPORE
8 Boon Lay Way #02-06 TradeHub 21
Singapore 609964
Tel: (65) 6272 9272 Fax: (65) 6278 5310



041-098-2791
Made From Recycled Material

www.USGBoral.com

USG BORAL
INNOVATION INSPIRED BY YOU.™