

Sheetrock® Paper Joint Tape



For strength and crack resistance in drywall joint treatment

- High tensile strength to resist tearing, stretching and distortion
- Wafer-thin paper for easier joint treatment
- Roughened surface for superior bond
- Accurately center-creased to improve corner treatment

Description

SHEETROCK® brand paper joint tape is a special fiber tape designed for use with USG joint compounds to reinforce joints and corners in gypsum drywall interiors. Also recommended for joint treatment in veneer finish systems subject to rapid drying conditions and where framing exceeds 16" (406 mm) spacing. SHEETROCK paper joint tape resists cracking and stretching and is lightly sanded for increased bond.

SHEETROCK paper joint tape is manufactured from special cross-fibered tape with high tensile strength, both with and across the paper grain. Its high porosity produces a superior bond while eliminating the need for perforations. It also provides exceptional wet strength, resists stretching, wrinkling and other distortions, lies flat and resists tearing under tools. Easy to apply, SHEETROCK paper joint tape's positive center creasing and uniform winding promotes accurate and trouble-free application to angles as well as flat joints.

Limitations

In cold weather and during gypsum panel application and joint finishing, temperatures within the building shall be maintained within the range of 55-70 °F (13-21 °C). Adequate ventilation shall be provided to carry off excess moisture.

Application

Position and apply SHEETROCK® gypsum panels in accordance with manufacturer's recommendations. Prepare joint compound following directions on container. Cover joint with a thin layer of compound and embed paper joint tape, leaving about 1/32" (0.7 mm) of compound under feathered edge. While embedding the tape, remove excess compound from edge and apply a thin coat over the tape. Let dry and sand lightly as required. Apply second coat, feathering approx. 2" (50 mm) beyond first coat. Let dry, sand lightly as required, and then apply third coat, feathering 2" (50 mm) beyond second coat. Sand lightly as required when dry. Finish fastener heads, corner bead, and inside corners as required with at least three coats of joint compound, feathered out onto panel faces and sanded as required to a smooth surface.

For painting and decorating, follow manufacturer's directions for materials used. All surfaces, including applied joint compound, must be thoroughly dry, dust-free, and not glossy before decorating. A prime coat of SHEETROCK® First Coat primer or a good quality interior latex flat wall paint with high solids content should be applied undiluted and allowed to dry before painting, texturing or wallpapering.

To improve fastener concealment where gypsum panel walls and ceiling will be subject to severe artificial or natural side lighting, and be decorated with a water-based paint, apply a skim coat of SHEETROCK® ready-mixed all purpose joint compound, SHEETROCK® MIDWEIGHT™ all purpose joint compound, SHEETROCK® PLUS 3™ lightweight all purpose joint compound or COVER COAT® compound or spray with SHEETROCK® TUFF-HIDE™ primer-surfacer prior to decoration.

Product Data

Material: Cross-fibered paper.

Coverage: Approx. 370 ft./1000ft² (121 m/100m²) gypsum panels.

Packaging	Type	Width in. (mm)	Length ft. (mm.)	No. of Units/Master Carton	Application
	Roll	2-1/16 (52)	75 (22.8)	24 rolls	Ideal for the occasional small drywall job, patching work, etc.
			250 (76.2)	20 rolls	Popular size for hand-application joint treatment. Weighs approximately 1-1/4 lbs. (0.6 kg) per roll.
			500 (152.4)	10 rolls	Designed to fit easily into taping machines with fewer roll changes. Weighs approximately 2-1/2 lbs. (1.2 kg) per roll so that machine balance is not disturbed.

Note: 1-31/32" (50 mm) width tape is available by special order. Contact your local sales office or representative for information on lead times and minimum quantity requirements.

Submittal Approvals:

Job Name		
Contractor		Date

Trademarks

The following trademarks used herein are owned by United States Gypsum or a related company: COVER COAT, MIDWEIGHT, PLUS 3, SHEETROCK, TUFF-HIDE, USG, USG in stylized letters.

Notice

We shall not be liable for incidental or consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from the date it was or reasonably should have been discovered.

Note

All products described here may not be available in all geographic markets. Consult your local sales office or representative for more information.

Safety First!

Follow good safety and industrial hygiene practices during handling and installing all products and systems. Take necessary precautions and wear the appropriate personal protective equipment as needed. Read material safety data sheets and related literature on products before specification and/or installation.



Manufactured by
United States Gypsum Company
550 West Adams Street
Chicago, IL 60661

USG Boral Singapore
8 Boon Lay Way #02-06 TradeHub 21
Singapore 609964
Tel: (65) 6272 9272
Fax: (65) 6278 5310

www.usgboral.com

J1736/rev. 10-10
© 2010, United States Gypsum Company
Printed in U.S.A.